

# Just Perfect.

**Endless Productivity Made Swift** 



The all-new 36" **imagePROGRAF TM-5355** and **TM-5350** large format printers empower every print delivery with enhanced scanning operability and printer processing power, delivering high quality CAD drawings, photos and posters. Redefine your workplace productivity with a seamless, swift and reliable print partner.

# **Printing Productivity Driven By Swift Efficiency**

Push printing productivity forward with the all-new 36" **imagePROGRAF TM-5355** and **TM-5350** large format printers, which offer powerful scanning and printing capabilities, alongside versatile multi-application printing for engineering firms to drive greater business efficiency overall.

### **Swift and Productive**

The new **L-COA PRO II high-speed imaging processing chip** facilitates swift startups from sleep mode as well as continuous printing by providing improved data processing power, improving overall printing efficiency.





#### **Print Speed**

**Conventional printers** 

TM-5350/TM-5355

More than 20% faster\*

\*Based on Canon internal testing using plain paper with continuous printing of A1 page per min

# **Enhancing Prints with Vivid Red**

The **brand new magenta ink** offers a more vivid red on CAD drawings, posters and photos that help to improve clarity and details.

# **Borderless Printing Made Easy**

**Borderless poster printing** on any size of roll paper is possible with the TM-5350 and TM-5355.




# **Making User Operation Easy**

The new design of the printer features a **flat top space** for roll paper replacement or for placing output prints.



The **automatic paper type detection** allows for easy viewing of paper media details and the balance of roll paper within the printer.



# **Smoother, Easier Workflows**

Streamline how you manage workflows with convenient and intuitive software applications.

#### **Direct Print Plus**

The Direct Print Plus feature allows you to **print PDF or JPEG files in batches** with custom templates with minimal effort.



#### **Free Layout Plus**

Documents can be resized easily with Free Layout Plus, which allows files to be dragged and dropped into the software for **easy document** resizing to specific paper layouts.



#### **Accounting Manager**


Monitor and **keep track of print usage** with ease using the
Accounting Manager application.



#### **PosterArtist**

#### **Design vibrant posters**

for your needs with minimal effort using the PosterArtist application.



Check it out at <a href="https://posterartist.canon">https://posterartist.canon</a>







# **Scanning with Efficiency**

The Lm36 scanner can be used with the TM-5350, which comes with improved scanning functions that boost productivity and operability through a maximum paper thickness of 0.8mm alongside featuring brand new transparent guides.



TM-5350 MFP Lm36

The **TM-5355** is able to utilise the **Z36 scanner** which offers easier troubleshooting by providing a **web manual link** when a printer error occurs. It also features a roll removal button, alongside effortless information retrieval of the **amount of roll paper remaining** in the printer.



TM-5355 MFP Z36

#### **SPECIFICATIONS**

		TM-5350 TM-5355		PRINT SPEED	*4 (A1 SIZE)	TM-5350	TM-5355
Printer Type		5-Colour, 36"			CAD Drawing		
Number of Nozzles		15,360 nozzles (MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each)			(A1 Landscape, Fast Q5 mode)	17 s	sec
Max. Print Resolution		2,400 x 1,200 dpi		Plain Paper	CAD Drawing	<u> </u>	
Nozzle Pitch		1,200 dpi x 2			(A0 Portrait, Fast Q5 mode)	32 sec	
Line Accurac			or less		Poster		
Ink Bottle	Sales Ink Bundle	130 mi / 300 mi (	MBK, BK, C, M, Y)	Heavyweight Coated Paper	(A0 Portrait,	2 min	33 sec
Size	Starter Ink	130 ml (MBK) / 9	0 ml (BK, C, M, Y)	MEDIA HANDI	Standard mode)		
Ink Type		Pigme	ent Ink		Roll Paper		
			t Graphic Raster)	Media Width	Cut Sheet	203.2 ~	917 mm
Print Languag	jes	HP-GL/2, HP RTL JPEG (Ver. JFIF1.02)		Media Roll Paper/ Thickness Cut Sheet Printable Roll Paper		0.07 ~ 0.8 mm	
J		CALS G4*2					
			- PDF rinter Driver (Win/Mac Versions), Direct Print Plus, Free Layout Plus,		Roll Paper Cut Sheet	203.2 mm ~ 18 m <sup>-15</sup> 279.4 ~ 1,600 mm	
Print Solution	is and	Printer Driver (win/mac versions), Direct Print Plus, Pree Layout Prins, PosterArtist Windows/Web & Lite, Wi-Fi Connection Assistant, PIXMA Cloud Link, Apple AirPrint (Mobile), Canon PRINT Inkjet/ SELPHY (Mobile), Canon Print System (Mobile), uniFlow Server		Media Length   Cut Sheet  Media Core Size  Outside Diameter Roll Paper		2 inch / 3 inch core	
Applications						150 mm or less	
		Media Configuration Tool (includes Color Customisation Tool), Accounting Manager, Device Management Console,		Media Feed	Roll Paper	1 Roll, Top Load, Front Output	
Management Solutions				Wedia Feed	Cut Sheet	Front Load, f	Front Output
		Quick Utility Toolbox  Hi-Speed USB, Full Speed (12 Mbit/sec), Hi-Speed (480 Mbit/sec),		Delivery Direct		Face-up, Front Side	
	USB B Port		Series B (4 pins)		Recommended Area	20 mm, 3 mm, 3 mm	
	USB A Port	_	USB Memory (Direct Print)		(Roll Paper)		
	302777070	IEEE AAA	Supported file format: JPEG/PDF 3 10base-T		Recommended Area		
	Network	IEEE 802.3u	100base-TX	Margins	(Cut Sheet)	,, =-	
Interface		(Top, Bottom, Side)		(Top, Bottom,	Printable Area (Roll Paper)	3 mm, 3 mm, 3 mm	
(Built-in)							
	Wireless LAN					0 n	nm
						3 mm, 20 mm, 3 mm	
			P (AES)*3 AP(AES)*3		(Cut Sheet)		
		WPA3-EAP(AES)*3		DIMENSIONS	(W x D x H) & W Printer (Main	1,462 x 1,122 x 801 mm	
Memory Hard Disk		2 GB 128 GB (Physical Memory 2 GB) No Hard Disk 500 GB (Encrpyted) Hard Disk		Packaged	unit + Stand		
Display			0.9 cm TFT color)	Dimensions	+ Basket + Pallet)	Weight	
z.op.u.y	Please visit	202 (110 111011)	0.0 0.11 11 1 00.01,		(SD-35)		
OS https://asia.					Printer	1,285 x 748 x 439 mm (Operation panel not tilted up)	
Compatibility	OS compatibility	Windows, Macintosh		Printer &	Printer with	Weight: 50 kg (Excluding print head and ink)	
and to download the latest drivers				Weight	Stand +	1,285 x 885 x 1,060 mm (Operation panel not tilted up / Basket operation panel not tilted up / Basket clo	
COANINED					Basket		
SCANNER					(SD-35)	Weight: 65 kg (Excludi	ng print noda ana inity
Scanner Mod	el	Lm36	Z36		(SD-35)		
Scanner Mod Scan Width		3	6"	Scanner & We		Weight: 65 kg (Excludi 1,238 x 253 x 131 mm Weight: 6.56 kg	1,056 x 251 x 156 mm Weight: 7.8 kg
Scanner Mod Scan Width Optical Resol		3 Up to 600 dpi	6" Up to 1200 dpi		ight	1,238 x 253 x 131 mm Weight: 6.56 kg	1,056 x 251 x 156 mm Weight: 7.8 kg
Scanner Mod Scan Width Optical Resol		3	6"	POWER & OPI	ight ERATING REQUII	1,238 x 253 x 131 mm Weight: 6.56 kg	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l
Scanner Mod Scan Width Optical Resol Scan Format	ution (DPI)	Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB,	POWER & OPI	ight ERATING REQUII	1,238 x 253 x 131 mm Weight: 6.56 kg	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5
Scanner Mod Scan Width Optical Resol Scan Format	ution (DPI)	Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG  Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)	POWER & OPI Power Supply Power Consumption	ight ERATING REQUII (Printer)	1,238 x 253 x 131 mm Weight: 6.56 kg REMENTS AC 100-240 V	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l (50 - 60 Hz)
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina	ution (DPI)	Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB,	POWER & OPI Power Supply Power	ight  ERATING REQUII (Printer)  Operation  Sleep Mode  Power OFF	1,238 x 253 x 131 mm Weight: 6.56 kg REMENTS AC 100-240 V < 65 W < 1.4	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l 7 (50 - 60 Hz) < 69 W 5 W
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina	ution (DPI)	Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP Colour	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks	POWER & OPI Power Supply Power Consumption (Printer) Recommended	ight  ERATING REQUII (Printer)  Operation  Sleep Mode  Power OFF  Temperature	1,238 x 253 x 131 mm Weight: 6.56 kg REMENTS  AC 100-240 V  < 65 W  < 1.4  < 0.0  15 - 3	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l 7 (50 - 60 Hz) < 69 W 5 W 1 W
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI)	Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/IPEG  Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit)	POWER & OPP Power Supply Power Consumption (Printer)	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V  < 65 W  < 1.1  < 0.  15 - 3  10 - 80% RH (no d	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l ( (50 - 60 Hz) < 69 W 5 W 1 W 20 °C ew condensation)
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina	ution (DPI)	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi):	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG  Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)	POWER & OPI Power Supply Power Consumption (Printer) Recommended	ight  ERATING REQUII (Printer)  Operation  Sleep Mode  Power OFF  Temperature	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V  < 65 W  < 1.6  < 0.0  15 - 3  10 - 80% RH (no d  Approx.	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l  ( (50 - 60 Hz)
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina	ution (DPI)	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec	6"  Up to 1200 dpi  TIFF, TIFF GA, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'7	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V  < 65 W  < 1.1  < 0.  15 - 3  10 - 80% RH (no d	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l  ( (50 - 60 Hz)
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG  Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit)  200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'7	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V  < 65 W  < 1.6  < 0.0  15 - 3  10 - 80% RH (no d  Approx.	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l  7 (50 - 60 Hz)  < 69 W  6 W  1 W  10 °C  ew condensation)  6.2 Bels  hdby 35 dB(A) or less
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Monochrome	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/IPEG  Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power <sup>77</sup> Pressure <sup>77</sup> CCESSORIES er	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V  < 65 W  < 1.0  < 0.  15 - 5  10 - 80% RH (no d  Approx.  Approx. 41 dB(A), Stat	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  / (50 - 60 Hz) < 69 W  6 W  11 W  10 °C ew condensation)  6.2 Bels hdby 35 dB(A) or less
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power" Pressure" Pressure" **CCESSORIES er + Basket	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V  < 65 W  < 1.0  < 0.0  15 - 3  10 - 80% RH (no d  Approx.  Approx. 41 dB(A), Star	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  ( (50 - 60 Hz)
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB  ScanAPP  Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi):	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec  Monochrome / Greyscale (8 bit) 200 dpi: 13 ips / 330.2 mm per sec 300 dpi: 86 ips / 218.4 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power" Pressure" Pressure" **CCESSORIES er + Basket	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1 < 0. 15 - 2 10 - 80% RH (no d Approx. Approx. 41 dB(A), Stai	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  / (50 - 60 Hz) < 69 W 6 W 11 W 10 °C ew condensation) 6.2 Bels hdby 35 dB(A) or less
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi):	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/PEG  Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit)  200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 13 ips / 330.2 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'7 PCESSORIES  er + Basket Interface	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V  < 65 W  < 1.0  < 0.0  15 - 3  10 - 80% RH (no d  Approx.  Approx. 41 dB(A), State  RH2	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  / (50 - 60 Hz) < 69 W 6 W 11 W 10 °C ew condensation) 6.2 Bels hdby 35 dB(A) or less
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	Jup to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Standard (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec  Monochrome / Greyscale (8 bit) 200 dpi: 13 ips / 330.2 mm per sec 300 dpi: 86 ips / 218.4 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'7 PCESSORIES  er + Basket Interface	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1  < 0.  15 - 3  10 - 80% RH (no d Approx. Approx. 41 dB(A), Star  RH2  RA-  Magenta: PFI-8121 (130	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l  7 (50 - 60 Hz)  < 69 W  5 W  1 W  10 °C  ew condensation)  6.2 Bels  ndby 35 dB(A) or less
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi):	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec Monochrome / Greyscale (8 bit) 200 dpi: 13 ips / 330.2 mm per sec 300 dpi: 8 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'7 PCESSORIES  er + Basket Interface	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1  < 0.  15 - 3  10 - 80% RH (no d Approx. Approx. 41 dB(A), Star  RH2  RA  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: Is	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  7 (50 - 60 Hz) < 69 W  6 W  1 W  10 °C ew condensation)  6.2 Bels hdby 35 dB(A) or less
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft	ution (DPI) tions ware	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 15 ips / 38.1 mm per sec Colour Draft (200 dpi): 1 ips / 25.4 mm per sec	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 13 ips / 330.2 mm per sec 600 dpi: 3 ips / 128.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'7 PCESSORIES  er + Basket Interface	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1  < 0.  15 - 3  10 - 80% RH (no d Approx. Approx. 41 dB(A), Star  RH2  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: IPF-	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  / (50 - 60 Hz) < 69 W  6 W  1 W  80 °C ew condensation)  6.2 Bels addby 35 dB(A) or less
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft Max. Copy Sp	ution (DPI) tions ware	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Colour Draft (200 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 12.7 mm per sec	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 300 dpi: 13 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec Colour (24 bit)  Colour (24 bit) 200 dpi: 3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' PCESSORIES  er + Basket Interface	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1  < 0.  15 - 3  10 - 80% RH (no d Approx. Approx. 41 dB(A), Star  RH2  RA  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: Is	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  / (50 - 60 Hz) < 69 W  3 W  1 W  0 °C ew condensation) 6.2 Bels adby 35 dB(A) or less  -2-3502  ml) / PFI-8321 (300 ml) PFI-8120 (130 ml) / PFI-8320 (300 ml) -06 -08
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft Max. Copy Sp (inch/sec) or	ution (DPI)  tions  ware  eed: (mm/sec)	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi):	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 13 ips / 330.2 mm per sec 600 dpi: 3 ips / 128.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance of	ight  ERATING REQUII (Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'? Pressure'? CCESSORIES  er + Basket Interface ES	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1  < 0.0  15 - 3  10 - 80% RH (no d Approx. Approx. 41 dB(A), Star  RH2  RA  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: PF- CT- MC	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  / (50 - 60 Hz) < 69 W  3 W  1 W  0 °C ew condensation) 6.2 Bels adby 35 dB(A) or less  -2-3502  ml) / PFI-8321 (300 ml) PFI-8120 (130 ml) / PFI-8320 (300 nl) -06 -08
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft Max. Copy Sp (inch/sec) or	eed: (mm/sec)	3 Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.3 ips / 8.38 mm per sec	6"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 300 dpi: 13 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec Colour (24 bit)  Colour (24 bit) 200 dpi: 3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader If for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance ( Specifications a " User adjustment " User adjustment	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' **CESSORIES  er + Basket interface  ES  Cartridge re subject to chants required. Printing	1,238 x 253 x 131 mm	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  1 (50 - 60 Hz)  < 69 W  3 W  1 W  10 °C  ew condensation) 6.2 Bels  ndby 35 dB(A) or less 35 02  ml) / PFI-8321 (300 ml) PFI-8120 (130 ml) / PFI-8320 (300 nl) -06  -08  -31
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft Max. Copy Sp (inch/sec) or	eed: (mm/sec)	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 2 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.33 ips / 8.38 mm per sec  Monochrome Draft (200 dpi):	G"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 300 dpi: 13 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec Colour (24 bit) 200 dpi: 3 ips / 76.2 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance Specifications a " User adjustmer Paper required	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF  Temperature Humidity Power' Pressure'7 Pressure'7 Pressure or the management of the manageme	1,238 x 253 x 131 mm	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  7 (50 - 60 Hz)  < 69 W  6 W  1 W  10 °C  ew condensation)  6.2 Bels  ndby 35 dB(A) or less 35 02  ml) / PFI-8321 (300 ml)  PFI-8120 (130 ml) / PFI-8320 (300 r  -06  -08  -31
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft Max. Copy Sp (inch/sec) or	eed: (mm/sec)	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB  ScanAPP  Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 15 ips / 38.1 mm per sec Best (600/600 dpi): 15 ips / 38.1 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.3 ips / 8.38 mm per sec  Monochrome Draft (200 dpi): 3 ips / 76.2 mm per sec	G"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 4.3 ips / 30.2 mm per sec	POWER & OPPower Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance of Specifications a " User adjustmer Paper required Paper required 2 USB Thumb dri	ERATING REQUII (Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure' CESSORIES  er + Basket Interface ES  Cartridge re subject to changes required. Printing I Plain paper and cover printing is not su	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1 < 0. 15 - 3 10 - 80% RH (no d Approx. Approx. 41 dB(A), Stat  RH2  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: I  CT-  Ge without notice. pervironment and media must match the ated paper only. pported.	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  1 (50 - 60 Hz)  < 69 W  3 W  1 W  10 °C  ew condensation) 6.2 Bels  ndby 35 dB(A) or less 35 02  ml) / PFI-8321 (300 ml) PFI-8120 (130 ml) / PFI-8320 (300 nl) -06  -08  -31
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft Max. Copy Sp (inch/sec) or	eed: (mm/sec)	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 2 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Colour Draft (200 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.3 ips / 8.38 mm per sec  Monochrome Draft (200 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec	G"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader If for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance of Specifications a " User adjustmer Paper required "2 USB Thumb dri "3 IEEE802.IX (EA	ight  ERATING REQUII (Printer)  Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure'  **CESSORIES**  er + Basket Interface  ES  Cartridge  re subject to chamits required. Printing: Plain paper and cove printing is not st.  prints one page does	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  < 1.1 < 0. 15 - 3 10 - 80% RH (no d Approx. Approx. 41 dB(A), Stat  RH2  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: I  CT-  Ge without notice. pervironment and media must match the ated paper only. pported.	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  1 (50 - 60 Hz)  < 69 W  3 W  1 W  30 °C  ew condensation) 6.2 Bels hdby 35 dB(A) or less 35 02  mi) / PFI-8321 (300 m) PFI-8120 (130 m) / PFI-8320 (300 m) ends31  sse used for the adjustments.
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft  Max. Copy Sp (inch/sec) or	eed: (mm/sec)	3 Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.3 ips / 8.38 mm per sec  Monochrome Draft (200 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Best (600 dpi): 1.5 ips / 38.1 mm per sec Best (600 dpi):	G"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 4.3 ips / 30.2 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment  Acoustics  OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader Ifor uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance a " User adjustmer Paper required "2 USB Thumb dri "3 IEEEB02.1X (EA "1 Time taken to pand pre-printin	ERATING REQUII (Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' **Pressure' **CESSORIES  er **+ Basket interface ES  Cartridge re subject to chan. ts required. Printing. Plain paper and cove printing is not su p-TLS/EAP-TTLS/F orint one page does g operation.	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  15 - 3 10 - 80% RH (no d Approx. Approx. 41 dB(A), Star  RA  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: I CT. MC  ge without notice. I environment and media must match the ated paper only. I poported.  EAP) supported.  EAP) supported.  not include time required for data proces	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 l  2 (50 - 60 Hz)  < 69 W  3 W  1 W  30 °C  ew condensation)  6.2 Bels  ndby 35 dB(A) or less 35 02  mi) / PFI-8321 (300 ml) PFI-8120 (130 ml) / PFI-8320 (300 ml)  asse used for the adjustments.
Scanner Mod Scan Width Optical Resol Scan Format Scan Destina Scanner Soft  Max. Copy Sp (inch/sec) or	eed: (mm/sec)	3  Up to 600 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 2 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Colour Draft (200 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.3 ips / 8.38 mm per sec  Monochrome Draft (200 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec	G"  Up to 1200 dpi  TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec	POWER & OPP Power Supply Power Consumption (Printer) Recommended Environment  Acoustics  OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader Ifor uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance a " User adjustmer Paper required "2 USB Thumb dri "3 IEEEB02.1X (EA "1 Time taken to pand pre-printin	ERATING REQUII (Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure' CESSORIES  er + Basket Interface ES  Cartridge re subject to changes and cover printing is not support to the printing in the printing of the OS and apply go peration, go to the OS and apply go the OS and apply go the OS and apply go to the	1,238 x 253 x 131 mm Weight: 6.56 kg  REMENTS  AC 100-240 V < 65 W  15 - 3 10 - 80% RH (no d Approx. Approx. 41 dB(A), Star  RA  Magenta: PFI-8121 (130 Matte Black / Black / Cyan / Yellow: I CT. MC  ge without notice. I environment and media must match the ated paper only. I poported.  EAP) supported.  EAP) supported.  not include time required for data proces	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5  1 (50 - 60 Hz)  < 69 W  3 W  1 W  30 °C  ew condensation) 6.2 Bels ndby 35 dB(A) or less 35 02  mi) / PFI-8321 (300 ml) PFI-8120 (130 ml) / PFI-8320 (300 nl) ends31  sse used for the adjustments.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Distributed by:



To find out more, visit www.computergraphics.com.ph









